

ACRYLOC® METAL & GALV PRIMER

PRODUCT TYPE

Primers & Undercoats

PACKAGING

15L Heavy Duty Plastic Pail

NOMINAL WEIGHT

22kg

DESCRIPTION

Acryloc *Metal & Galv Primer* is designed for priming Zinalume®, galvanised iron and other metal surfaces prior to application of subsequent topcoats.

Acryloc *Metal & Galv Primer* is a water based acrylic coating containing inorganic rust passivators & inhibitors, adhesion promoters and inert fillers.

FEATURES & BENEFITS

- Strong adhesion
- Easy to apply
- Water based
- Easy & safe cleanup

SUITABLE SUBSTRATES

- Zinalume® & Galvanised Iron
- Iron & Steel
- Colorbond®

Where applying to a roof, it is recommended that Rainwater tanks be disconnected from the guttering system before commencing work as material could be split on the roof or washed off if rain falls before the coating is fully cured. The guttering should remain disconnected until after application of all subsequent coatings and until all residues are washed from the guttering. It is safe to collect drinking water once the finish coating has cured.

SUBSTRATE PREPARATION

- Areas not to be coated should be masked and protected
- All surfaces to be coated must be clean, sound, free from contaminants including; oil, mould release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material
- Surface rust should be removed and passivated by using Acryloc Rust Converter
- Care should be taken to keep Acryloc *Metal & Galv Primer* off windows and adjacent surfaces that are not to be coated, as it can be very difficult to remove once allowed to dry

APPLICATION

- Acryloc *Metal & Galv Primer* does not require thinning or dilution

Method

- Mix thoroughly with a broad, flat stirrer, using an upward lifting action
- Acryloc *Metal & Galv Primer* can be applied using a roller, brush, HVLP spray equipment or airless spray equipment
- If using spray equipment, an 18 thou tip and white gun filter is recommended
- Acryloc *Metal & Galv Primer* must be over-coated with appropriate products from the coating system being used

Important Notes

- Do not apply Acryloc *Metal & Galv Primer* on exposed surfaces when rain is anticipated within 6 hours of completion of the days work, longer in damp, cold +/- or humid conditions
- Avoid application in full sun, on hot surfaces or in hot windy conditions
- Application should be carried out on a day with temperatures above 10°C and below 32°C
- Coated area must be protected from damage until the completion of the project; finished work must be protected from rain, frost and severe weather conditions until fully dried

Clean-Up

Clean up with water

OTHER CONSIDERATIONS**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly.

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for *Acryloc Metal & Galv Primer*

TECHNICAL DATA

APPEARANCE	Viscous grey coloured liquid		
ODOUR	Low		
APPLICATION METHODS	Roller, brush, spray		
SPECIFIC GRAVITY (NOMINAL)	1.3 -1.5		
THEORETICAL COVERAGE	6.5-10m ² /L per single coat		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Overcoat	Fully Dried
	N/A	When dry	N/A
NO. OF COATS	Typically 1 coat		
GLOSS LEVEL	Matt		

SAFETY & HANDLING

Refer to **MSDS** for *Acryloc Metal & Galv Primer* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

When working with *Acryloc Metal & Galv Primer* observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

Refer to **MSDS** for *Acryloc Metal & Galv Primer* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products

174 Cavan Rd

DRY CREEK

South Australia 5094

P: +61 8 8368 0222

F: +61 8 8349 4260

E: sales@acryloc.com.au

W: www.acryloc.com.au