

ACRYLOC[®] DECKING OIL

PRODUCT TYPE

Solvent Based

PACKAGING

4L, 10L Steel Can

NOMINAL WEIGHT

3.8kg, 9kg respectively

DESCRIPTION

Acryloc *Decking Oil* is a solvent based timber coating, designed to replace the natural oils lost through weathering of bare timber. Application of Acryloc *Decking Oil* will give a clear, natural finish with little or no gloss.

APPLICATION

The dryness of all timbers, new and weathered, can vary greatly.

Before applying the first coat or recoating, try a small test patch with a thin coat.

Check to see that the *Decking Oil* soaks into the timber completely and does not leave a sticky surface.

- Can be used on interior or exterior surfaces.
- Application on rough sawn timber is best done by brush.
- Can be rolled onto Smooth timber.
- If spraying, follow directly after with brush or roller while still wet to ensure good coverage and penetration.
- It is best to wait 24 hours before recoating, though dry exterior timber may be recoated sooner.
- Coverage ranges from 12-20 square metres per litre depending on how dry the timber is.

Clean-Up

Clean up with Mineral Turps.

CAUTION

Acryloc *Decking Oil* is **FLAMMABLE**. Rags contaminated with *Decking Oil* may self-ignite if kept in a confined space. All rags must be immersed in water or spread out to dry in the open air.

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

SAFETY & HANDLING

Refer to **MSDS** for **Acryloc Decking Oil** before use. When working with **Acryloc Decking Oil** observe the usual precautions for handling solvent or turps based products including:

- Keep out of reach of children.
- Avoid inhalation of the vapour. Provide adequate ventilation during use.
- Avoid skin and eye contact. The use of protective goggles is recommended.
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

FIRST AID MEASURES

Refer to **MSDS** for **Acryloc Decking Oil** for detailed information.

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Contact a doctor or Poisons Information Centre.

Eyes

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

DISTRIBUTED BY:

Bizfine Pty Ltd, T/A Acryloc Building Products
174 Cavan Rd
DRY CREEK, South Australia 5094

P: +61 8 8368 0222

F: +61 8 8349 4260

E: sales@acryloc.com.au W: www.acryloc.com.au