

ACRYLOC[®] PAVING PAINT

PRODUCT TYPE

Solvent Based

PACKAGING

4L, 10L Steel Can

NOMINAL WEIGHT

4.3kg, 10kg respectively

DESCRIPTION

Acryloc *Paving Paint* is a single pack polyurethane coating, suitable for concrete and timber floors such as pathways, driveways, showrooms, patios and workshops.

Acryloc *Paving Paint* gives a tough, semi gloss finish which repels water and oils.

Paving Paint is available in a range of colours to suit both home and commercial applications.

APPLICATION

- Can be used on interior or exterior surfaces.
- Concrete should be acid etched and high pressure cleaned. New concrete should be weathered for 2-3 months.
- Bare timber will require priming or undercoating.
- Application by brush or roller is recommended. If spraying, follow directly after with a roller while still wet to ensure good coverage and finish.
- For steep and very smooth surfaces, fine sand should be sprinkled on between coats.
- Recoat and foot traffic after 30 minutes to 3 hours depending on conditions.
- Coverage ranges from 6-13 square metres per litre depending on the surface condition.

Clean-Up

Clean up with Mineral Turps.

CAUTION

Acryloc *Paving Paint* is **FLAMMABLE**. Rags contaminated with *Paving Paint* may self-ignite if kept in a confined space. All rags must be immersed in water or spread out to dry in the open air.

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

SAFETY & HANDLING

Refer to **MSDS** for **Acryloc Paving Paint** before use. When working with **Acryloc Paving Paint** observe the usual precautions for handling solvent or turps based products including:

- Keep out of reach of children.
- Avoid inhalation of the vapour. Provide adequate ventilation during use.
- Avoid skin and eye contact. The use of protective goggles is recommended.
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

FIRST AID MEASURES

Refer to **MSDS** for **Acryloc Paving Paint** for detailed information.

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Contact a doctor or Poisons Information Centre.

Eyes

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

DISTRIBUTED BY:

Bizfine Pty Ltd, T/A Acryloc Building Products
174 Cavan Rd
DRY CREEK, South Australia 5094

P: +61 8 8368 0222

F: +61 8 8349 4260

E: sales@acryloc.com.au W: www.acryloc.com.au