

## ACRYLOC® LIQUID PIGMENT

### PRODUCT TYPE

Colourants & Additives

### PACKAGING

1000L Intermediate Bulk Container  
200L Steel Drums

### NOMINAL WEIGHT

1700 - 1800kg  
330 - 370kg

### DESCRIPTION

Acryloc Liquid Pigment is formulated to provide an easy to dispense colourant for the manufacture of cement blocks, pavers, concrete and mortar mixes and similar products. A range of standard colours is available with a nominal content of 50% pigment by weight. Other colours can be made to order (minimum order quantities apply).

### TECHNICAL DATA

APPEARANCE	Coloured Viscous liquid
ODOUR	Low
SPECIFIC GRAVITY (NOMINAL)	~1.65
WEIGHT SOLIDS (APPROX)	51%, Nominally 50% pigment by weight
SOLVENT FOR CLEANING	Water
FLAMMABILITY	Non-flammable

### OTHER CONSIDERATIONS

#### Shelf-Life – Unopened Containers

Maximum two (2) years from date of manufacture when stored correctly

#### Transport & Storage

Containers should not be stacked during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for *Acryloc Liquid Pigment*

### SAFETY & HANDLING

Refer to **MSDS** for *Acryloc Liquid Pigment* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit [www.acryloc.com.au](http://www.acryloc.com.au)

When working with *Acryloc Liquid Pigment* observe the following precautions as a minimum:

- Avoid prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

### FIRST AID MEASURES

Refer to **MSDS** for *Acryloc Liquid Pigment* before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on 1300 661 745 or visit [www.acryloc.com.au](http://www.acryloc.com.au)

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

#### Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

#### Advice to Doctor

Treat symptomatically

### MANUFACTURED BY:

Bizfine Pty Ltd, T/A Acryloc Building Products  
174 Cavan Rd  
DRY CREEK, South Australia 5094

P: +61 8 8368 0222

F: +61 8 8349 4260

E: [sales@acryloc.com.au](mailto:sales@acryloc.com.au) W: [www.acryloc.com.au](http://www.acryloc.com.au)